University of Minnesota Nano Center

Hard Bake Oven-Standard Operating Procedure

Badger Name: n/a **Revision:** 4

Model: Lab-Line Duo-Vac Revisionist: Laura Parmeter Location: Keller-Bay 2 Date: March 25, 2020

Table of contents

- **1.** Scope
- 2. Tool description
- **3.** Safety
- 4. Restrictions
- 5. Tools and Equipment
- 6. Procedure
 - **6.1.** Setup
 - **6.2.** Operating Instructions
- 7. Problems/Troubleshooting

University of Minnesota Nano Center

Hard Bake Oven-Standard Operating Procedure

1. Scope

1.1. This document provides detailed instructions on how to properly operate the Hard Bake Oven.

2. Tool description

2.1. This is an exhausted oven with a monitored temperature setting of 120 °C. There is a center rack for placing substrate boats. The left dial, the Control Thermostat is set at 50 °C the right dial, the Dial Safety is set at 70 °C.



Figure 1 The ovens in Keller Hall-Bay 2.

3. Safety

3.1. Take caution when unloading your hot substrates when the bake time is complete.

University of Minnesota Nano Center

Hard Bake Oven-Standard Operating Procedure

4. Restrictions

4.1. Wafers may have material on the surface that could outgas fumes such as photoresist.

This oven is exhausted.

4.2. Do not change the temperature of this oven; it is to remain at 120 °C.

5. Tools and Equipment

- **5.1.** 120V electrical outlet.
- **5.2.** Quartz boat (optional)

6. Procedure

6.1. Setup

- **6.1.1.** Place your substrate perpendicular in the quartz boats provided or place them on a handmade foil boat.
- **6.1.2.** Users must supply their own method of timing the length of bake.

6.2. Operating Instructions

6.2.1. Open the door and place substrates in the oven on the rack and close the door.

7. Problems/Troubleshooting

7.1. If the settings are not at the above set point, notify MNC staff.