



Microlithography Chemical Corp.

1254 Chestnut Street
Newton, MA 02164-1418
Tel: (617) 965-5511
Fax: (617) 965-5818

MATERIAL SAFETY DATA SHEET

PAGE 1
13 June 1996

SECTION 1. CHEMICAL IDENTIFICATION -----

CHEMICAL NAME: Organic Polymer Solution
TRADE NAME: NANO™ PMGI SF6
PRODUCT #: Positive Radiation Sensitive Resist
G113106

SECTION 2. COMPOSITION-----

HAZARDOUS
INGREDIENTS: Cyclopentanone (CAS: 120-92-3); 75-80%.
Tetrahydrofurfuryl alcohol (CAS: 97-99-4); 10-15%

OTHER
INGREDIENTS: Polyaliphatic imide copolymer (CAS: 123209-67-6)
Proprietary Surfactant, <1%

SECTION 3. HAZARD DATA-----

INFLAMMABILITY: Flammable liquid.
SKIN CONTACT: May cause skin irritation.
EYE CONTACT: May cause serious damage to the eyes.
INGESTION: May be harmful if swallowed.
INHALATION: Irritating to mucous membranes and upper respiratory tract.
MUTAGENICITY: Not known to be mutagenic.
CARCINOGENICITY: Not considered carcinogenic by NTP, IARC and OSHA
OTHER: Repeated or prolonged contact or exposure to vapors of
tetrahydrofurfuryl alcohol may cause central nervous system
depression and decreased male fertility.

TARGET ORGANS: Eyes, Nervous System, Respiratory Tract, Reproductive

SECTION 4. FIRST AID MEASURES-----

INHALATION: If inhaled, remove to fresh air. If patient has stopped breathing,
give artificial respiration. If breathing is difficult give oxygen.
Contact physician immediately.

INGESTION: Wash out mouth with water if conscious. Get medical attention
immediately.

SKIN CONTACT: Rinse with water for 15 minutes while removing contaminated
clothing and shoes. Wash affected area with soap and water. Wash
contaminated clothing.

EYE CONTACT: Rinse immediately with water, flush for 15 min. lifting eyelids
frequently. Get emergency medical assistance.

MATERIAL SAFETY DATA SHEET

PAGE 2
13 June 1996

CHEMICAL NAME: Organic Polymer Solution
TRADE NAME: NANO™ PMGI SF6
Positive Radiation Sensitive Resist
PRODUCT #: G113106

SECTION 5. FIRE FIGHTING MEASURES-----

EXTINGUISHING

MEDIA:

Dry chemical, carbon dioxide, foam.

SPECIAL FIRE FIGHTING PRECAUTIONS:

Wear self-contained breathing apparatus (SCBA) and personal protective equipment to prevent contact with skin and eyes.

UNUSUAL FIRE OR EXPLOSION HAZARDS:

Vapor may travel considerable distance to source of ignition and flash back. Heat will build pressure and may rupture closed containers. Forms explosive mixtures in air. Keep containers cool with water spray.

SECTION 6. ACCIDENTAL RELEASE PROCEDURES -----

Evacuate Area.

Eliminate all ignition sources.

Wear self-contained breathing apparatus (SCBA), rubber boots, and heavy rubber gloves. Avoid eye or skin contact. Cover with dry absorbent material and collect in closed container for disposal using non-sparking tools. Ventilate area and wash spill site after material pickup is complete, rinse with water. All clean-up should be carried out in accordance with federal, state, and local regulations. If required proper authorities should be notified.

SECTION 7. STORAGE AND HANDLING PRECAUTIONS-----

STORAGE:

Store in tightly closed container in a cool environment away from direct sunlight.

HANDLING:

Keep away from heat, sparks, and flames.

Do not breathe vapors.

Use only with mechanical exhaust.

Do not contact with skin, eyes, and clothing.

Severe eye irritant.

Avoid prolonged or repeated exposure.

Wear heavy rubber gloves.

Wash with soap and water after handling.

Have safety shower and eye wash available.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION-----

RESPIRATORY PROTECTION:

In case of spills, use of self-contained breathing apparatus (SCBA) is recommended.

VENTILATION:

Local or general mechanical ventilation is required.

SKIN PROTECTION:

Heavy rubber gloves are highly recommended.

EYE PROTECTION:

Safety goggles are highly recommended.

MATERIAL SAFETY DATA SHEET

PAGE 3
13 June 1996

CHEMICAL NAME: Organic Polymer Solution
TRADE NAME: NANO™ PMGI SF6
Positive Radiation Sensitive Resist
PRODUCT #: G113106

SECTION 9. PHYSICAL AND CHEMICAL DATA

APPEARANCE: Pale yellow to yellow liquid
ODOR: Slightly sweet
BOILING POINT: 131-178 °C (268-352 °F)
SPECIFIC GRAVITY: 0.980
VAPOR PRESSURE: 8.7 mm @ 20 °C (68 °F)
VAPOR DENSITY: 2.3 (air=1)
H₂O SOLUBILITY: 40-50% @ 20 °C, by wt.
% VOLATILES: 94% by wt
EVAPORATION RATE: 1 (BuAc=1)
FLASH POINT: 30 °C (87 °F) TCC
AUTOIGNITION TEMP: 550 °C (1022 °F)
EXPLOSION LIMITS: 1.3 lower
unk. upper

SECTION 10. REACTIVITY DATA

STABILITY: Stable
INCOMPATIBILITY: Strong Oxidizing Agents, Strong Bases, Strong
Reducing Agents
HAZARDOUS POLYMERIZATION: Will not occur
HAZARDOUS COMBUSTION OR
DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide

SECTION 11. TOXICITY HAZARDS

ACUTE EFFECTS:

May be harmful if swallowed, inhaled, or absorbed through the skin.

Irritating to eyes and respiratory tract. May cause serious damage to the eyes.

Vapor or mist is irritating to the eyes, mucous membranes and upper respiratory tract.

Eye and skin contact can cause headache, nausea, vomiting, dizziness, weakness, drowsiness, narcosis, and loss of coordination in humans.

Causes moderate skin irritation in rabbits.

Prolonged and/or repeated exposure can cause absorption of harmful amounts of material.

SUBCHRONIC EFFECTS: Subchronic exposures (oral, dermal and inhalation) at relatively high levels have demonstrated systemic toxicity, reproductive toxicity, and central nervous system depression in either rats, rabbits or dogs.

ORAL: LD50 (mam): 2000 mg/Kg as Cyclopentanone
LD50 (rat) 1600 mg/Kg as Tetrahydrofurfuryl alcohol
IRRITATION: skin: 500 mg - mild
eyes: 100 mg/ 4 sec - severe

TLV: ACGIH (TWA) none established
PEL: OSHA (8hr TWA) none established

MATERIAL SAFETY DATA SHEET

PAGE 4
13 June 1996

CHEMICAL NAME: Organic Polymer Solution
TRADE NAME: NANO™ PMGI SF6
PRODUCT #: Positive Radiation Sensitive Resist
G113106

SECTION 12. ECOLOGICAL DATA-----

No data available at this time

SECTION 13. DISPOSAL CONSIDERATIONS-----

Burn in an EPA-licensed chemical incinerator equipped with an afterburner and scrubber at an approved waste disposal facility. Observe all federal, state, and local environmental regulations.

SECTION 14. TRANSPORTATION INFORMATION-----

HAZARD CLASSIFICATION: Flammable Liquid
SHIPPING NAME: Resin Solution
UN NUMBER: UN 1866
PACKING GROUP: III

SECTION 15. REGULATORY INFORMATION-----

HAZARDOUS LISTINGS: All ingredients appear on the TSCA Inventory of Chemical Substances, EINECS, and the Japan Hazardous Chemical Listing.
SARA Title III: This product IS NOT subject to SARA Title III, Section 313 Reporting Requirements.

Calif. SCAQMD Rule 443.1 VOC's: 920 g/l; vapor pressure 8.7 mm Hg @ 20 °C

SECTION 16. ADDITIONAL PRECAUTIONS AND COMMENTS-----

To the best of our knowledge, the above information is believed to be accurate but does not claim to be all inclusive and is intended to be used only as a guide. The supplier makes no warranty of any kind, expressed or implied, concerning the use of this product and shall not be held liable for any damage resulting from handling or from contact with the above product. User assumes all risks incident to its use.