

Material Safety Data Sheet

May be used comply with
OSHA's Hazard Communication Standard
29 CFR 1910.1200. Standard must be
consulted for specific requirements

U.S.Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List) PLANARIZING COATING PC3-1500		<i>Note:</i> Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.			
Section I					
Manufacturer's Name Futurrex, Inc.		Emergency Telephone Number 800-535-5053			
Address (Number, Street, City, State and ZIP Code) 12 Cork Hill Road		Telephone Number for Information 973-209-1563			
Franklin , New Jersey 07416		Date Prepared 1/2/2009			
		Signature of Prepare (optional)			
Section II - Hazardous Ingredients/Identity Information					
Hazardous Components (Specific Chemical Identity: Common Name(s))		OSHA PEL	ACGIH TLV	CAS Number	% (optional)
n-Butyl Acetate		15 Oppm	200 ppm	123-86-4	
Proprietary Resin		Not Established		Proprietary	
*All Components of the product are registered in the Chemical Substance Inventory according with the Toxic Substance Control Act.					
Section III - Physical/Chemical Characteristics.					
Boiling Point (°C)	126	Specific Gravity (H2O=1)		<1	
Vapor Pressure (mm Hg) (20°C)	8	Melting Point (°C)		-73.5	
Vapor Density (AIR-1)	4	Evaporation Rate (Butyl Acetate=1)		1	
Solubility in Water 0,68% at 20°C					
Appearance and Odor Light yellow color. Characteristic odor.					
Section IV- Fire and Explosion Hazard Data					
Flash Point (Method Used) 26°C (TCC)		Flammable Limits. (% volume in air)	LEL 1.7	UEL 7.6	
Extinguishing Media. Carbon dioxide, dry chemical media, alcohol-type or all-purpose-type foam.					
Special Fire Fighting Procedures . Use water spray to cool fire-exposed containers and structures. Use self contained breathing apparatus and protective coating.					
Unusual Fire and Explosion Hazard. Flammable vapors may be heavier than air and may travel long distance along the ground before igniting and may flash back to the vapor source.					