

**PRINTOGANTH MV BASIC TP1**

Version 1.0
SDS_US_GHS

SDS Number: 1684944

Revision Date: 05/26/2015

SECTION 1. IDENTIFICATION

Product name : PRINTOGANTH MV BASIC TP1

Product code : 1684944

Manufacturer or supplier's details

Company name of supplier : Atotech Deutschland GmbH

Address : Erasmusstrasse 20
Berlin 10553
Germany

Telephone : +4930349850

Company name of supplier : Atotech USA

Address : 1750 OVERVIEW DRIVE
ROCK HILL, SC, USA 29730

Telephone : +18038173500

Prepared by
Product Safety Department (PSD): product-safety@atotech.com

Inquiries
Questions about content of Safety Data Sheets: product-safety@atotech.com

Emergency telephone : CHEMTREC +18004249300

Transport Medical : Rocky Mountain Poison Control Center: 303-623-5716

Recommended use of the chemical and restrictions on use

Recommended use : Plating agents and metal surface treating agents
Surface treatment

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Corrosive to Metals : Category 1

Skin corrosion : Category 1A

**PRINTOGANTH MV BASIC TP1**

Version 1.0

SDS_US_GHS

SDS Number: 1684944

Revision Date: 05/26/2015

Serious eye damage : Category 1

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Reproductive toxicity : Category 1B

GHS Label element

Hazard pictograms



Signal Word : Danger

Hazard Statements : H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H350i May cause cancer by inhalation.
H360 May damage fertility or the unborn child.

Precautionary Statements : **Prevention:**
P202 Do not handle until all safety precautions have been read and understood.
P234 Keep only in original container.
P260 Do not breathe dust or mist.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P285 In case of inadequate ventilation wear respiratory protection.

Response:
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor/ physician.

Storage:
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

**PRINTOGANTH MV BASIC TP1**

Version 1.0
SDS_US_GHS

SDS Number: 1684944

Revision Date: 05/26/2015

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Aqueous solution

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Sodium hydroxide	1310-73-2	≥ 5 - < 10
Nickel sulfate	7786-81-4	≥ 0.1 - < 1

This product may contain component (s) that are not listed under disclosure. All components not listed, do not contain hazardous materials above de minimus disclosure limits as defined by OSHA, NIOSH, ACGIH or Canadian WHMIS regulations and or guidelines. Please refer to other sections of the MSDS for information on safety, health and environmental guidelines and precautions.

SECTION 4. FIRST AID MEASURES

General advice : Call a physician or poison control center immediately.
Show this material safety data sheet to the doctor in attendance.

If inhaled : Call a physician or poison control center immediately.
Move to fresh air.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.
Take off contaminated clothing and shoes immediately.
Consult a physician.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 60 minutes.
Consult a physician.

If swallowed : If swallowed, call a poison control center or doctor immediately.
Never give anything by mouth to an unconscious person.
Do not induce vomiting without medical advice.

Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Causes serious eye damage.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause cancer by inhalation.
May damage fertility or the unborn child.
Causes severe burns.

Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing

**PRINTOGANTH MV BASIC TP1**

Version 1.0

SDS_US_GHS

SDS Number: 1684944

Revision Date: 05/26/2015

Notes to physician : For specialist advice physicians should contact the Poison Control Center.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : No information available.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use a water spray to cool fully closed containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).
- Environmental precautions : Should not be released into the environment. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Avoid formation of aerosol. Dam up. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Clean contaminated floors and objects thoroughly while observing environmental regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Handle in accordance with good industrial hygiene and safety practice. In case of insufficient ventilation, wear suitable respiratory

**PRINTOGANTH MV BASIC TP1**

Version 1.0

SDS_US_GHS

SDS Number: 1684944

Revision Date: 05/26/2015

equipment.
Avoid breathing mist or vapors.

Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-ventilated place.
Keep locked up or in an area accessible only to qualified or authorized persons.
May be corrosive to metals.

Recommended storage temperature : -5 - 40 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Sodium hydroxide	1310-73-2	C	2 mg/m3	ACGIH
		C	2 mg/m3	NIOSH REL
		TWA	2 mg/m3	OSHA Z-1
		C	2 mg/m3	OSHA P0
Nickel sulfate	7786-81-4	TWA	1 mg/m3 (Nickel)	OSHA Z-1
		TWA (Inhalable fraction)	0.1 mg/m3 (Nickel)	ACGIH
		TWA	0.1 mg/m3 (Nickel)	OSHA P0
		TWA	0.015 mg/m3 (Nickel)	NIOSH REL

Personal protective equipment

Respiratory protection : In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection
Remarks

: Wear protective gloves. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Follow the instructions for use issued by the producer.

Eye protection

: Tightly fitting safety goggles
Face-shield
Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection

: Impervious clothing
Apron
Boots

**PRINTOGANTH MV BASIC TP1**

Version 1.0

SDS_US_GHS

SDS Number: 1684944

Revision Date: 05/26/2015

Protective measures / Engineering measures : Ensure adequate ventilation, especially in confined areas.

Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
When using do not eat, drink or smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : light green

Odor : No information available.

Odor Threshold : No data available

pH : 12 - 14

Melting point/freezing point : not determined

Initial boiling point and boiling range : not determined

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : ca. 23 hPa (20 °C)

Relative vapor density : No data available

Density : 1.225 - 1.265 g/cm³

Solubility(ies)
Water solubility : completely miscible

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : No data available

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

**PRINTOGANTH MV BASIC TP1**

Version 1.0

SDS_US_GHS

SDS Number: 1684944

Revision Date: 05/26/2015

Viscosity, kinematic : No data available

Oxidizing properties : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : May be corrosive to metals.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Gives off hydrogen by reaction with metals.
Potential for exothermic hazard

Conditions to avoid : To avoid thermal decomposition, do not overheat.

Incompatible materials : Acids
MetalsHazardous decomposition products : Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation

Eye contact

Skin Absorption

Acute toxicity

Not classified based on available information.

Product:Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method**Ingredients:****Nickel sulfate:**

Acute oral toxicity : LD50 Oral (Rat): 275 mg/kg

Acute inhalation toxicity : Acute toxicity estimate : 1.5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Remark: The acute toxicity estimate (ATE) of the ingredients are derived using the LD50/LC50 values where available.

Skin corrosion/irritation

Causes severe burns.

**PRINTOGANTH MV BASIC TP1**

Version 1.0
SDS_US_GHS

SDS Number: 1684944

Revision Date: 05/26/2015

Product:

Remarks: Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Product:

Remarks: Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC

Group 1: Carcinogenic to humans

Nickel sulfate

7786-81-4

ACGIH

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA specified

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

Known to be human carcinogen

Nickel sulfate

7786-81-4

Reproductive toxicity

May damage fertility or the unborn child.

Ingredients:**Nickel sulfate:**

Reproductive toxicity - Assessment : May damage the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

**PRINTOGANTH MV BASIC TP1**

Version 1.0

SDS_US_GHS

SDS Number: 1684944

Revision Date: 05/26/2015

Aspiration toxicity

Not classified based on available information.

Further information**Product:**Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****Nickel sulfate:**

Toxicity to fish : LC50: 1.28 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50: 1 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae : EC50: 0.75 mg/l
Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.
Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION**International Regulation**

**PRINTOGANTH MV BASIC TP1**

Version 1.0

SDS_US_GHS

SDS Number: 1684944

Revision Date: 05/26/2015

UNRTDG

UN number : UN 1824
Proper shipping name : SODIUM HYDROXIDE SOLUTION
Class : 8
Packing group : II
Labels : 8

IATA-DGR

UN/ID No. : UN 1824
Proper shipping name : Sodium hydroxide solution
Class : 8
Packing group : II
Labels : Corrosive
Packing instruction (cargo aircraft) : 855
Packing instruction (passenger aircraft) : 851

IMDG-Code

UN number : UN 1824
Proper shipping name : SODIUM HYDROXIDE SOLUTION
Class : 8
Packing group : II
Labels : 8
EmS Code : F-A, S-B
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**DOT / 49 CFR**

UN/ID/NA number : UN 1824
Proper shipping name : Sodium hydroxide solution
Class : 8
Packing group : II
Labels : CORROSIVE
ERG Code : 154
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

TSCA 5a : Not relevant

TSCA_12b : Not relevant

DEA : Not applicable

EPCRA - Emergency Planning and Community Right-to-Know**CERCLA Reportable Quantity**

Ingredients	CAS-No.	Component RQ	Calculated product RQ
-------------	---------	--------------	-----------------------



PRINTOGANTH MV BASIC TP1

Version 1.0

SDS_US_GHS

SDS Number: 1684944

Revision Date: 05/26/2015

		(lbs)	(lbs)
Sodium hydroxide	1310-73-2	1000	*
Nickel sulfate	7786-81-4	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Nickel sulfate 7786-81-4

Massachusetts Right To Know

Sodium hydroxide 1310-73-2 5 - 10 %

Pennsylvania Right To Know

Sodium hydroxide 1310-73-2 5 - 10 %

New Jersey Right To Know

Sodium hydroxide 1310-73-2 5 - 10 %
Nickel sulfate 7786-81-4 0.1 - 1 %

California Prop 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

Nickel sulfate 7786-81-4

Remarks: Components which are only displayed in Section 15 are being reported for local regulatory purposes. These components are not displayed in Section 3 due to one or more of the following conditions being met: being present in the product at concentration(s) below threshold limit values for reporting, not considered hazardous materials, health hazards or because they do not contribute to the overall GHS Classification of the final product as required by OSHA HazCom 2012 final rule (29 CFR 1910.1200).

Substances currently restricted by WEEE/RoHS (European Directive 2002/96/EC , 2002/95/EC) or ELV (European Directive 2000/53/EC):

PBDE	PBB	CrVI	Hg	Pb	Cd
-	-	-	-	-	-


Please note: Current legislation restricting the use of certain substances applies to „homogeneous material“ in finished articles being supplied to the market. Substances deposited during surface finishing may have a composition (weight percent) higher than the weight percent of the substance in the operating solution from which the deposit is made. Atotech encourages its customers to implement systems to ensure their finished products comply with the regulations in force.

**PRINTOGANTH MV BASIC TP1**

Version 1.0
SDS_US_GHS

SDS Number: 1684944

Revision Date: 05/26/2015

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

HEALTH	3
FLAMMABILITY	0
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date : 05/26/2015

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.