

**BREWER SCIENCE INC.  
SAFETY DATA SHEET**

This Material Safety Data Sheet has been prepared to comply with the EC Directive, Canadian WHMIS and the OSHA Hazard Communication Standard.

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION  
AND THE COMPANY/UNDERTAKING**

**Product Name:** ProTEK™ Primer

**Manufacturer:** Brewer Science, Inc.  
2401 Brewer Drive  
Rolla, MO 65401

**Information Phone Number:** (573) 364-0300

**Fax:** (573) 368-3318

**Emergency Phone Number:** (800) 255-3924

**MSDS Date of Preparation:** 11/20/03

**Product Use:** Protective Coating

**SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

| Chemical Name   | CAS# / EINECS#       | %     | EU Classification<br>(67/548/EEC) |
|---|----------------------|-------|-----------------------------------|
| 1-Methoxy-2-propanol<br>(Propylene glycol monomethyl ether, PGME) | 107-98-2 / 203-539-1 | 80-95 | R10                               |
| Polymer   | Proprietary          | 0-2   | Xi R41, R37/38                    |
| Catalyst  | Proprietary          | <.1   |                                   |

See Section 16 for further information on EU Classification.

**SECTION 3: HAZARDS IDENTIFICATION**

Liquid with a solvent odor.

**EMERGENCY OVERVIEW:** Flammable liquid and vapor. May cause eye, skin, and respiratory irritation. May cause headache, dizziness, nausea and other symptoms of central nervous system depression.

**EU Preparation Classification (1999/45/EC):** Flammable R10

**SECTION 4: FIRST AID MEASURES**

**Eye:** Rinse thoroughly with water for at least 15 minutes, holding the eye lids open to be sure the material is washed out. Get immediate medical attention.

**Skin:** Remove contaminated clothing. Wash contact area thoroughly with soap and water. Get medical attention if irritation or symptoms of exposure develop. Launder clothing before re-use.

**Inhalation:** Remove victim to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

**Ingestion:** Do not induce vomiting unless directed to do so by medical personnel. Keep the victim calm and warm. Get immediate medical attention.

**SECTION 5: FIRE FIGHTING MEASURES**

**Flash Point:** 32°C (90°F)

**Flammable Limits:** LEL: 1.5 vol % UEL: 10.9 vol %

**Extinguishing Media:** Use water fog or spray, alcohol foam, carbon dioxide or dry chemical.

**Special Fire Fighting Procedures:** Wear NIOSH approved, positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

**Unusual Fire Hazards:** Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. Vapors may form explosive mixtures with air in confined areas.

**Hazardous Decomposition Products:** Oxides of carbon and nitrogen, organic acid vapors, methanol and unknown materials.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

**Spill:** Remove all ignition sources such as open flames, spark producing equipment, pilot lights, etc. Wear appropriate protective clothing to prevent eye and skin contact including impervious gloves, safety goggles and respirator if needed. Ventilate area. Cover with and inert absorbent material and collect into an appropriate container for disposal. Report spills and releases as required to appropriate authorities.

#### SECTION 7: HANDLING AND STORAGE

**Handling:** Avoid breathing vapors, aerosols and mists. Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Always wear impervious gloves, chemical safety goggles and protective clothing when handling this material. Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep product away from heat, sparks, flames and all other sources of ignition. No smoking in storage or use areas. Keep containers closed when not in use.

**Storage:** Store in a cool, dry, well-ventilated location away from incompatible materials. Keep containers closed when not in use.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| Chemical Name        | Exposure Limits  |
|----------------------|--|
| 1-Methoxy-2-propanol | 100 ppm TLV-TWA, 150 ppm TLV-STEL<br>100 ppm DFG MAK<br>100 ppm EU-TWA, 150 ppm EU-STEL skin |
| Polymer              | None Established (PEL/TLV)   |

**Ventilation:** Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits. Use explosion proof electrical equipment and wiring where required.

**Respiratory Protection:** If needed, a NIOSH approved respirator with organic vapor cartridges may be used. For higher exposures (greater than 10 times the TLV), a supplied air respirator may be required. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

**Skin Protection:** Impervious gloves are recommended. Based on available test data, 4H or Silver Shield gloves are suggested.

**Eye Protection:** Chemical safety goggles recommended.

**Other Protective Equipment:** Impervious clothing is recommended to prevent skin contact and contamination of personal clothing. An eye wash facility and safety shower should be available in the work area.

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**Appearance and Odor:** Liquid with a solvent odor.

**pH:** Not available

**Boiling Point:** 120 - 150°C

**Vapor Pressure:** 12.5 mmHg @ 25°C (1-Methoxy-2-propanol)

**Vapor Density:** 3.12 (1-Methoxy-2-propanol)

**Specific Gravity:** Not available

**Melting Point:** Not Applicable

**Water Solubility:** Partially Soluble

**Evaporation Rate:** Not available

#### SECTION 10: STABILITY AND REACTIVITY

**Stability:** Stable: X Unstable:

**Incompatibility/Conditions to Avoid:** Strong oxidizing agents, acids, alcohols and bases. Keep away from heat, sparks, flames and other sources of ignition.

**Hazardous Decomposition Products:** Oxides of carbon and nitrogen, organic acid vapors, methanol and unknown materials.



Hazardous Polymerization: May Occur: Will not occur: X

#### SECTION 11: TOXICOLOGICAL INFORMATION

##### Potential Health Effects:

**Eye:** May cause moderate eye irritation. Corneal injury is unlikely.

**Skin:** May cause mild irritation. 1-Methoxy-2-propanol may be absorbed through the skin causing symptoms of headache, dizziness, nausea, and drowsiness.

**Inhalation:** Inhalation of vapors, mists, or aerosols may cause nose and throat irritation with the possibility of central nervous system depression. Symptoms of central nervous system depression include headache, dizziness, drowsiness, nausea and unconsciousness.

**Ingestion:** Swallowing may cause gastrointestinal irritation and central nervous system depression with symptoms similar to those described under inhalation.

**Chronic Hazards:** Chronic exposure may cause nervous system, kidney or liver effects based on studies with laboratory animals.

**Carcinogen Status:** None of the components of this product are listed as carcinogens by OSHA, IARC or NTP.

**Medical Conditions Aggravated by Exposure:** Pre-existing skin diseases.

##### Acute Toxicity Values:

1-Methoxy-2-propanol: Oral rat LD50 - 5660 mg/kg

Inhalation rat LC50 - 10,000 ppm/5 hr

Skin rabbit LD50 - 13 gm/kg

Polymer: No data available

#### SECTION 12: ECOLOGICAL INFORMATION

1-Methoxy-2-propanol: LC50 for fathead minnow is 20800 mg/L and for daphnia magna is 23300 mg/L.

#### SECTION 13: DISPOSAL INFORMATION

Dispose in accordance with all local, state and federal regulations.

#### SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: 1-Methoxy-2-propanol Solution

ERG #129

DOT Hazard Class: 3, PG III

UN Number: UN3092

DOT Labels Required (49CFR172.101): Flammable Liquid

Hazardous Substance (49CFR172.101): None

Reportable Quantity: N/A

IATA Shipping Name: 1-Methoxy-2-propanol Solution

IATA Hazard Class: 3, PG III

UN Number: UN3092

IATA Hazard Labels Required: Flammable Liquid

#### SECTION 15: REGULATORY INFORMATION

##### U.S. FEDERAL REGULATIONS:

CERCLA 103 Reportable Quantity: Not applicable

##### SARA TITLE III:

Hazard Category for Section 311/312: Acute Health, Fire Hazard

**Section 313 Toxic Chemicals:** This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None

**Section 302 Extremely Hazardous Substances (TPQ):** None

**EPA Toxic Substances Control Act (TSCA) Status:** All of the components of this product are listed on the TSCA inventory.

**STATE REGULATIONS:**

**California Proposition 65:** This products contain the following substances known to the State of California to cause cancer: Aniline less than 0.02%.

**INTERNATIONAL REGULATIONS:**

**European Community Labeling:**

|  |   |
|--|---|
|  | R10 Flammable<br>S51 Use only in well ventilated areas. |
|--|---|

|                                      |
|--------------------------------------|
| <b>SECTION 16: OTHER INFORMATION</b> |
|--------------------------------------|

|                                 |                  |                |
|---------------------------------|------------------|----------------|
| <b>HMIS Ratings:</b> Health - 2 | Flammability - 3 | Reactivity - 0 |
| <b>NFPA Ratings:</b> Health - 2 | Flammability - 3 | Reactivity - 0 |

**EU Classes and Risk Phrases for Reference (See Sections 2 and 3):**

T Toxic

R10 Flammable

R37/38 Irritating to respiratory system and skin.

R41 Risk of serious damage to eyes.

=====

This above information is believed to be correct but does not propose to be all inclusive and shall be used only as a guide. Brewer Science shall not be held liable for any damage resulting from handling or from contact with the above product.