

TECHNIC, INC.

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product Name: TECHNISTAN AG BRIGHTENER

Product Code: 405426

Recommended use: Electroplating bath component; for industrial use only.

Supplier:

Technic Inc.

1 Spectacle Street

Cranston, RI 02910 USA

Telephone no: 401-781-6100

Current SDS preparation date: May 26, 2015

Original SDS preparation date: May 26, 2015

Emergency no: ChemTrec 800-424-9300, Outside the USA and Canada 703-527-3887

SECTION 2. HAZARD IDENTIFICATION

Classification:

Skin Corrosion/Irritation, Category 1C

Eye Damage/Irritation, Category 1

Label elements and precautionary statements:

Signal word: Danger

Pictogram(s):



Hazards not otherwise classified: None

Hazard statement(s):

Causes severe skin burns and eye damage

Precautionary statement(s):

Do not breathe dust, fume, gas, mist, vapors or spray.

Wash hands thoroughly after handling.

Wear protective gloves, clothing and eye and face protection.

If swallowed: Rinse mouth. DO NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

Wash contaminated clothing before reuse.

If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a poison center or doctor/physician.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Dispose of contents and container in accordance with local, state and federal regulations.

SECTION 3. COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical name	CAS Number	EINECS Number	Concentration
Methanesulfonic acid	75-75-2	200-898-6	4%

The chemical identity and concentration of one or more ingredients of this product are withheld as a trade secret under the provisions of paragraph (i) of 29 CFR 1910.1200. This information will be made available to health professionals and others in accordance with the applicable provisions of this paragraph.

SECTION 4. FIRST AID MEASURES

Inhalation:

Remove patient to fresh air. Support breathing if required. Obtain medical treatment for dizziness, unconsciousness or irritation or difficulty in breathing.

Skin contact:

Remove contaminated clothing and wash affected area thoroughly with soap and water. Launder clothing before rewearing. Seek medical attention for prolonged skin irritation.

Eye contact:

Flush with water, including under lids, for fifteen minutes. Obtain immediate medical attention.

Ingestion:

If patient is conscious, rinse mouth and drink at least two large glasses of water. DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Obtain immediate medical attention.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Use media appropriate for surrounding fire such as foam, extinguishing powder, carbon dioxide or water spray. In case of fire, cool endangered containers with water spray.

Unsuitable extinguishing media: High pressure water jet.

Specific hazards in case of fire: May emit toxic fumes under fire conditions.

Special protective equipment and precaution for fire fighters: For fires in enclosed areas, wear self-contained breathing apparatus and full protective gear. Do not inhale combustion gases.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Wear appropriate skin, eye and respiratory protection. Do not eat, drink or smoke while cleaning up.
Ensure adequate ventilation.

Methods and materials for containment and cleaning up:

Wear appropriate personal protective gear including eye, skin and respiratory protection. Contain spilled material and collect by absorption or other suitable method. Flush spill area with water. Do not allow this material or its rinsings to enter storm or sanitary sewers or other waterways. (See also Section 13).

Environmental precautions:

Prevent spills and rinsings from entering storm or sanitary sewers or other waterways and contact with soil.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling:

Avoid contact with eyes. Avoid prolonged repeated skin contact and breathing mists or vapors.
Use in well-ventilated area. Do not empty waste into sanitary drains.

Conditions for safe storage, including incompatibilities:

Store in a cool, dry area. Use with adequate ventilation. Keep container tightly closed when not in use.
Store only in the original container.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits:

Ingredient

ACGIH TLV

OSHA PEL

Other Limits

There are no exposure limits established for the ingredients in this material.

Appropriate engineering controls:

Use in well-ventilated area with local exhaust.

Respiratory protection: Wear appropriate, approved respirator when ventilation is inadequate.

Eye protection:

Chemical splash goggles or safety glasses with side shields must be worn.

Skin protection:

Wear rubber or neoprene gloves. Wear rubber apron and long sleeves to prevent skin contact. Wash hands thoroughly with soap and water after handling and before eating or smoking.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Color: Pale yellow
Odor: None
Odor threshold: Not available
pH: 1.0-1.5
Melting/freezing point: Not determined
Initial boiling point: Not determined
Flash point: Not applicable
Evaporation rate: Not available
Flammability (solid, gas): Not applicable
Upper/lower explosion limits: Non-explosive
Vapor pressure: Not determined
Vapor density: Not determined
Relative density (H₂O = 1) @25 °C: 1.05+/-0.05
Solubility: Completely soluble in water at 20 °C
Partition coefficient octanol/water: Not determined
Auto-ignition temperature: Not applicable
Decomposition temperature: Not available
Viscosity: Similar to water

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Stable, non-reactive when stored and used according to recommendations.
Chemical stability: No decomposition if used according to specifications.
Possibility of hazardous reactions: None are known.
Conditions to avoid: Excessive heat.
Incompatible materials: Strong oxidizing agent.
Hazardous decomposition products: Oxides of carbon and sulfur may be released when heated to dryness.

SECTION 11. TOXICOLOGICAL INFORMATION

Routes of Exposure and Symptoms

Inhalation: Vapor or mist causes burning and irritation of the upper respiratory system.
Ingestion: Produces severe burns to mouth, throat, stomach and gastrointestinal tract.
Skin Contact: Causes severe skin burns.
Eye Contact: Causes severe eye damage.

Acute and Chronic Effects from Short- and Long-term Exposure:

See Routes of Exposure and Symptoms above.

Acute Oral Toxicity: No applicable information available.
Acute Dermal Toxicity: No applicable information available.
Acute Inhalation Toxicity: No applicable information available.
Acute Eye Irritation: No applicable information available.

Product Name: TECHNISTAN AG BRIGHTENER
Product Code: 405426

Current SDS Version Date: May 26, 2015

Dermal Irritation: No applicable information available.

Carcinogen Listings: No applicable information available.

IARC: No

NTP: No

OSHA: No

Reproductive Effects: No applicable information available.

Target Organ Effects: No applicable information available.

SECTION 12. ECOLOGICAL INFORMATION

Aquatic Toxicity: There are no data reported for this material.

Persistence and degradability: There are no data reported for this material.

Bio-accumulative potential: There are no data reported for this material.

Mobility in soil: Accidental spillage may lead to penetration in the soil and groundwater. However, improper handling and disposal of this material may cause environmental damage.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal:

Disposal of this material is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

SECTION 14. TRANSPORT INFORMATION

Classification for shipment by road or rail, sea (IMDG) and air (IATA/ICAO):

UN proper shipping name: Corrosive Liquid, Acidic, Organic, N.O.S. (Contains Methane Sulfonic Acid)
UN number: UN3265
Transport hazard class: 8
Packing group: III

Marine Pollutant: No

Product Name: TECHNISTAN AG BRIGHTENER
Product Code: 405426

Current SDS Version Date: May 26, 2015

SECTION 15. REGULATORY INFORMATION

Inventory Status:

All components are on TSCA, EINECS/ELINCS, AICS, and DSL.

U.S. Regulations:

U.S. Superfund Amendments and Reauthorization Act (SARA) Title III:

SARA (311/312) HAZARD CATEGORIES:

☐ None ☒ Immediate ☐ Delayed ☐ Fire ☐ Reactive ☐ Pressure generating

SARA 313: This product contains the following SARA 313 Toxic Release Chemicals.

Chemical Name	CAS Number	Concentration
None		

The following product components are cited on the lists below:

Chemical Name	CAS Number	List Citations
None		California Proposition 65 List

SECTION 16. OTHER INFORMATION

VOC (Volatile Organic Compounds): None

HMIS Ratings:

Health: 3 **Flammability:** 0 **Reactivity:** 0 **Personal Protection:** C

Prepared by: Allan H. Reed

SDS Preparation date: May 26, 2015

Supersedes previous version: New SDS.

This SDS contains revisions in the following section(s): Not applicable. New SDS.

The information contained herein is accurate to the best of our knowledge. Technic Inc. makes no warranty of any kind, express or implied, concerning the safe use of this material in any process or in combination with other substances.

End of Safety Data Sheet