



Microlithography Chemical Corp.

1254 Chestnut Street
Newton, MA 02164-1418
Tel: (617) 965-5511
Fax: (617) 965-5818

MATERIAL SAFETY DATA SHEET

PAGE 1
22 February 1997

SECTION 1. CHEMICAL IDENTIFICATION

CHEMICAL NAME: Organic Resin Solution
TRADE NAME: XP SU-8 100

PRODUCT #: Y131273

SECTION 2. COMPOSITION

INGREDIENTS: Gamma Butyrolactone (CAS:96-48-0); 20-25%.
Mixed Triarylsulfonium/ Hexafluoroantimonate Salt;
(CAS: 89452-37-9)/(CAS: 71449-78-0)/
Propylene Carbonate (CAS: 108-32-7); 1-5%
Epoxy Resin (CAS: 28906-96-9); 70-75%

SECTION 3. HAZARD DATA

INFLAMMABILITY: Combustible liquid.
SKIN CONTACT: May cause skin irritation.
EYE CONTACT: Severe eye irritant.
INGESTION: May be harmful if swallowed in large quantities.
INHALATION: May cause irritation..
MUTAGENICITY: Not known to be mutagenic.
CARCINOGENICITY: Not considered carcinogenic by NTP, IARC and OSHA
OTHER:
TARGET ORGANS: Eyes, Epidermis.

SECTION 4. FIRST AID MEASURES

INHALATION: No occupational exposure limits have been developed for this material. Where exposure through inhalation may occur from use, NIOSH approved respiratory equipment is recommended.

INGESTION: If a large quantity swallowed, give lukewarm water. DO NOT induce vomiting. Risk of damage to lungs exceeds poisoning risk. Get medical attention immediately.

SKIN CONTACT: Rinse with water for 15 minutes while removing contaminated clothing and shoes. Wash affected area with soap and water. Wash contaminated clothing.

EYE CONTACT: Rinse immediately with water, flush for 15 min. lifting eyelids frequently. Get emergency medical assistance. Prompt action is essential.

MATERIAL SAFETY DATA SHEET

PAGE 2
22 February 1997

CHEMICAL NAME: Organic Resin Solution
TRADE NAME: XP SU-8 100

PRODUCT #: Y131273

SECTION 5. FIRE FIGHTING MEASURES-----

EXTINGUISHING

MEDIA:

Dry chemical, carbon dioxide, foam, water spray, fog.

SPECIAL FIRE FIGHTING
PRECAUTIONS:

Do not enter fire area without proper protection. Fight fire from a safe distance/protected location. Heat may build enough pressure to rupture closed containers, spreading fire, increasing risk of burns/injuries. Use water spray/fog for cooling. Avoid frothing, steam explosion. Burning liquid may float on water. Although water soluble, may not be practical to extinguish fire by water dilution. Notify authorities immediately if liquid enters sewer, public waters.

UNUSUAL FIRE OR
EXPLOSION HAZARDS:

Heat from fire can generate flammable vapor. When mixed with air and exposed to ignition source, vapors can burn in open or explode if confined. Vapors may be heavier than air. May travel long distances along the ground before igniting and flashing back to vapor source. Fine sprays/mists may be combustible at temperatures below normal flash point.

SECTION 6. ACCIDENTAL RELEASE PROCEDURES -----

Evacuate Area.

Eliminate all ignition sources.

Wear self-contained breathing apparatus (SCBA), rubber boots, and heavy rubber gloves. Avoid eye or skin contact. Cover with dry absorbent material and collect in closed container for disposal using non-sparking tools. Ventilate area and wash spill site after material pickup is complete, rinse with water. All clean-up should be carried out in accordance with federal, state, and local regulations. If required proper authorities should be notified.

SECTION 7. STORAGE AND HANDLING PRECAUTIONS-----

STORAGE:

Store in tightly closed container in a cool environment away from direct sunlight.

HANDLING:

Use only under yellow light.

Keep away from heat, sparks, and flames.

Use only with mechanical exhaust.

Do not contact with skin, eyes, and clothing.

Severe eye irritant.

Avoid prolonged or repeated exposure.

Wear heavy rubber gloves.

Wash with soap and water after handling.

Have safety shower and eye wash available.

MATERIAL SAFETY DATA SHEET

PAGE 3
22 February 1997

CHEMICAL NAME: Organic Resin Solution
TRADE NAME: XP SU-8 100

PRODUCT #: Y131273

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

RESPIRATORY PROTECTION: In case of spills, use of self-contained breathing apparatus (SCBA) is recommended.
VENTILATION: Local or general mechanical ventilation is required.
SKIN PROTECTION: Rubber gloves are recommended.
EYE PROTECTION: Safety goggles are highly recommended.

SECTION 9. PHYSICAL AND CHEMICAL DATA

APPEARANCE: Pale yellow to clear
ODOR: Slightly sweet
BOILING POINT: 204 °C (400 °F)
SPECIFIC GRAVITY: 1.2332
VAPOR PRESSURE: 2 mm @ 20 °C (68 °F)
H₂O SOLUBILITY: 20-30% by wt
% VOLATILES: 20-30% by wt
EVAPORATION RATE: 1 (BuAc=1)
FLASH POINT: 98 °C (209 °F) TCC
AUTOIGNITION TEMP: 437 °C (820 °F)
EXPLOSION LIMITS: 3.6 lower
16 upper

SECTION 10. REACTIVITY DATA

STABILITY: Stable
INCOMPATIBILITY: Strong Oxidizing Agents, Strong Bases, Strong Acids
HAZARDOUS POLYMERIZATION: Will not occur
HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS: Carbon Monoxide, Aldehydes, Acids, Hydrogen Fluoride Gas.

MATERIAL SAFETY DATA SHEET

PAGE 4
22 February 1997

CHEMICAL NAME: Organic Resin Solution
TRADE NAME: XP SU-8 100

PRODUCT #: Y131273

SECTION 11. TOXICITY HAZARDS

Gamma Butyrolactone

In animal studies, due to the rate of dermal absorption of GBL, dermal toxicity is assumed to be essential equal to oral toxicity. In humans, oral ingestion of solutions containing high concentrations of GBL has caused reversible coma.

Mixed Triarylsulfonium/Hexafluoroantimonate Salt/Propylene Carbonate

This material was mutagenic in the Ames bacterial assay. It is inactive, however, in the in vivo mouse micronucleus test.

SECTION 12. ECOLOGICAL DATA

No data available at this time.

SECTION 13. DISPOSAL CONSIDERATIONS

Burn in an EPA-licensed chemical incinerator equipped with an afterburner and scrubber at an approved waste disposal facility. Observe all federal, state, and local environmental regulations.

SECTION 14. TRANSPORTATION INFORMATION

HAZARD CLASSIFICATION:	Not Regulated
SHIPPING NAME:	Resin Solution
UN NUMBER:	Not Regulated
PACKING GROUP	Not Regulated

SECTION 15. REGULATORY INFORMATION

HAZARDOUS LISTINGS:	All ingredients appear on the TSCA Inventory of Chemical Substances, EINECS, and the Japan Hazardous Chemical Listing.
SARA Title III:	This product IS NOT subject to SARA Title III, Section 313 Reporting Requirements.
Calif. SCAQMD Rule 443.1 VOC's:	350 g/l; vapor pressure 2 mm Hg @ 20 °C

MATERIAL SAFETY DATA SHEET

PAGE 5
22 February 1997

CHEMICAL NAME: Organic Resin Solution
TRADE NAME: XP SU-8 100

PRODUCT #: Y131273

SECTION 16. ADDITIONAL PRECAUTIONS AND COMMENTS-----

To the best of our knowledge, the above information is believed to be accurate but does not claim to be all inclusive and is intended to be used only as a guide. The supplier makes no warranty of any kind, expressed or implied, concerning the use of this product and shall not be held liable for any damage resulting from handling or from contact with the above product. User assumes all risks incident to its use.