

MATERIAL SAFETY DATA SHEET
AZ(R) P4400 PHOTORESISTSubstance key: BBG70L8
Version 1REVISION DATE: 06/23/2005
Print Date: 03/08/2006**Section 01 - Product Information****Identification of the company:**AZ Electronic Materials USA Corp.
70 Meister Avenue
Somerville, NJ 08876
Telephone No.: 800-515-4164**Information on the substance/preparation**

Product Safety: 908-429-3562

Emergency Tel. number: 800-424-9300 CHEMTREC**Trade name:** AZ(R) P4400 PHOTORESIST**Section 02 - Composition information****Hazardous ingredients:**

Chemical Name	CAS-no. (Trade secret no.)	Concentration [%]
1-Methoxy-2-propanol acetate	108-65-6	66.00

Section 03 - Hazardous identification**Emergency overview:**

OSHA combustible liquid; DOT flammable liquid., Amber-red liquid with characteristic odor., Irritating on contact or inhalation., Partially dissolves in water leaving a floating viscous mass.

Expected route of entry**Skin contact:**

Causes skin irritation.

Ingestion:

May be harmful if swallowed.

Inhalation:

Single exposure unlikely to be hazardous., High vapor concentration causes irritation to the nose, throat, and lungs.

Eye contact:

Causes eye irritation.

Health effects of exposure:**Component information:**

MATERIAL SAFETY DATA SHEET
AZ(R) P4400 PHOTORESIST



Substance key: BBG70L8
Version 1

REVISION DATE: 06/23/2005
Print Date: 03/08/2006

Eye: Causes eye irritation. Skin: Causes skin irritation. Ingestion: May be harmful if swallowed. Inhalation: Single exposure unlikely to be hazardous. High vapor concentration causes irritation to the nose, throat, and lungs. Systemic Effects: No hazard in normal industrial use. Reproductive & birth defects: Exposures having no adverse effect on the mother should have no effect on the fetus.

1-Methoxy-2-propanol acetate (108-65-6)

1-Methoxy-2-propanol acetate (PGMEA) can cause skin, eye, and respiratory irritation. Extreme or prolonged exposure may cause gastric and central nervous system effects. Long term, high level exposure to PGMEA has resulted in adverse effects to the livers and kidneys of experimental animals. PGMEA is readily absorbed through intact skin.

Listed carcinogen: IARC: NO NTP: NO OSHA: NO

HMIS:

Health: 2 Flammability: 2 Reactivity: 0 Personal protection: X

NFPA:

Health: 2 Flammability: 2 Reactivity: 0 Special notice: NONE

Section 04 - First aid measures

After inhalation: Remove victim to fresh air.
Consult physician if irritation occurs.

After contact with skin: Immediately remove contaminated clothing. Flush affected area thoroughly with water. After flushing with water, remove residue with soap and water. If necessary, clean area with a cloth or paper towel wetted with acetone. Assure adequate ventilation. Dispose of cloth/towel in a suitable receptacle. Consult physician if exposure is extensive or if irritation occurs.

After contact with eyes: Flush thoroughly with water for 15 minutes. Get immediate medical help.

After ingestion: If person is conscious, give water or milk to dilute stomach contents.
Never give anything by mouth to an unconscious person.
Consult physician.

Section 05 - Fire fighting measures

Flash point: 112 °F
Method: closed cup

MATERIAL SAFETY DATA SHEET
AZ(R) P4400 PHOTORESIST



Substance key: BBG70L8
Version 1

REVISION DATE: 06/23/2005
Print Date: 03/08/2006

Suitable extinguishing media:	Carbon dioxide, water, alcohol resistant foam, dry chemical.
Special fire fighting procedure:	Use self-contained breathing apparatus and full protective clothing. Use water spray to cool drums in fire area.
Specific hazards during fire fighting:	Thermal decomposition may generate carbon dioxide, carbon monoxide, and oxides of nitrogen and sulfur.
Unusual fire and explosion hazards:	Solvent vapors., Emits toxic fumes under fire conditions.

Section 06 - Accidental release measures

Steps to be taken in case of spill or leak:	Wearing appropriate personal protective equipment, contain spill, ventilate area of spill or leak, remove all sparking devices or ignition sources, collect onto inert absorbent, and place in a suitable container.
--	--

Section 07 - Handling and Storage

Advice on safe handling:

Keep away from heat and flame.
Avoid breathing vapors and contact with skin, eyes, and clothing.
Use only with adequate ventilation and proper protective eyewear, gloves, and clothing.
Wash thoroughly after handling.
Keep container closed.

Further information for storage conditions:

Store at appropriate temperature. See label for details.
Store in original container.
Transport and store under dry conditions tightly closed and protected from heat and light.
Pressure may build up slowly in closed containers due to gradual decomposition. This is accelerated by heat and light. May liberate combustible solvent vapors.

Section 08 - Exposion Control / personal protection

Skin and body protection:	Clothing suitable to prevent skin contact.
Advice on system design:	Use local exhaust ventilation.

MATERIAL SAFETY DATA SHEET
AZ(R) P4400 PHOTORESIST



Substance key: BBG70L8
Version 1

REVISION DATE: 06/23/2005
Print Date: 03/08/2006

Section 09 - Physical and chemical properties

Form:	Liquid
Color:	Clear, amber-red
Odor:	Strong, characteristic odor.
Water solubility:	The solvent is water soluble but the product forms two layers.
Starts to boil:	134 °C
Evaporation number:	Reference substance: n-butyl acetate app.
Vapor pressure:	2.4 Torr
Viscosity, dynamic:	150 mPas
Loss on drying:	66 %

Section 10 - Stability and reactivity

Hazardous reactions:	Stable.
Hazardous polymerization:	Will not occur.
Conditions to avoid:	Avoid contact with oxidizing agents. Avoid contact with strong acids. Avoid contact with alkaline materials.

Section 11 - Toxicological information

Acute oral toxicity:	Based on data from components this material is considered, not harmful (rat acute oral LD50 > 5000 mg/kg).
Acute inhalation toxicity	Based on data from components, this material is considered, not harmful (LC50 greater than 10,000 ppm or 200 mg/L). Based on component data, material is considered irritating to the respiratory tract.
1-Methoxy-2-propanol acetate (108-65-6)	
Acute oral toxicity:	LD50 rat (male) 8,500 mg/kg
1-Methoxy-2-propanol acetate (108-65-6)	

MATERIAL SAFETY DATA SHEET
AZ(R) P4400 PHOTORESIST



Substance key: BBG70L8
Version 1

REVISION DATE: 06/23/2005
Print Date: 03/08/2006

Acute oral toxicity: LD50 rat (female)
10,000 mg/kg

1-Methoxy-2-propanol acetate (108-65-6)
Acute inhalation toxicity LC50 rat
> 4350 ppm

1-Methoxy-2-propanol acetate (108-65-6)
Acute dermal toxicity: LD50 rabbit
> 5 mg/kg

Section 12 - Ecological information

1-Methoxy-2-propanol acetate (108-65-6)
Toxicity to fish: (Fathead minnow)
161 mg/l

1-Methoxy-2-propanol acetate (108-65-6)
Toxicity of aquatic invertebrates: (Daphnia magna)
400 mg/l

Section 13 - Disposal considerations

Product: Consult local, state, and federal regulations.
For disposal, this material is a flammable hazardous waste
under RCRA.

Section 14 - Transport information

Land transport

- **DOT:**
Not restricted

Sea transport

- **IMDG:**
UN-No: 1993
Proper technical name: FLAMMABLE LIQUID, N.O.S. contains (1-Methoxy-2-propanol acetate)
Class: 3
Packaging group: III
Marine pollutant:

MATERIAL SAFETY DATA SHEET
AZ(R) P4400 PHOTORESIST



Substance key: BBG70L8
Version 1

REVISION DATE: 06/23/2005
Print Date: 03/08/2006

EmS: F-E, S-E
MFAG:
Labels: 3

Air transport

▪ ICAO/IATA-DGR:
UN/ID No.: UN 1993
Proper technical name: FLAMMABLE LIQUID, N.O.S. contains (1-Methoxy-2-propanol acetate)
Class: 3
Packaging group: III
Labels: 73H

Section 15 - Regulatory information

TSCA Status: All components of this product are listed on the TSCA Inventory.

SARA (section 311/312): Reactive hazard: no
Pressure hazard: no
Fire hazard: yes
Immediate/acute: yes
Delayed/chronic: no

SARA 313 information: This product is not subject to SARA Title III Section 313 reporting requirements under 40 CFR 372.

Volatile organic compounds: Content VOC (g/l): 670 g/l
Method: calculated

Section 16 - Other information

Label information

CAUTION!

COMBUSTIBLE LIQUID AND VAPOR HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN Contains material that, based on animal data, can cause skin, eye, and respiratory irritation. Prolonged or repeated overexposure may cause gastric and central nervous system effects.

Keep away from heat and flame. Avoid breathing vapor. Avoid contact with skin, eyes, and clothing. Use only with adequate ventilation, and proper protective eyewear, gloves, and clothing. Wash thoroughly after handling. Keep container closed.

MATERIAL SAFETY DATA SHEET
AZ(R) P4400 PHOTORESIST



Substance key: BBG70L8
Version 1

REVISION DATE: 06/23/2005
Print Date: 03/08/2006

In case of contact, flush eyes with plenty of water for 15 minutes. Get medical attention immediately. Flush affected skin areas with water, and wash with mild soap and water. Remove contaminated clothing. If INHALED, remove individual to fresh air. If breathing is difficult, give oxygen. If ingested, give water or milk to dilute stomach contents. Never give anything by mouth to an unconscious person. Get medical attention immediately for ingestion or breathing problems or if skin contact is extensive.

In case of fire, use water, alcohol resistant foam, dry chemical, or CO2.

If spilled, wear protective clothing, remove ignition sources, prevent sparks, and ventilate area. Absorb with inert material, collect, and place in a chemical waste container.

Keep sealed in original container. Product must be kept refrigerated until use. Temperature range for refrigeration is 30 to 55 F (- 1 to 13 C). Allow product to reach ambient temperature prior to use. Empty container may contain harmful residue.

The solvent in this product is not photochemically reactive per Rule 102 of the California South Coast Air Quality Management District.

This information is supplied under the OSHA Hazard Communication Standard, 29 CFR 1910.1200, and is offered in good faith based on data available to us that we believe to be true and accurate. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable to the material. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate for that use. No warranty, express or implied, is made regarding the accuracy of this data, the hazards connected with the use of the material, or the results to be obtained from the use thereof. We assume no responsibility for damage or injury from the use of the product described herein. Data provided here are typical and not intended for use as product specifications. (R) and TM indicate trademarks of AZ Electronic Materials USA Corp., its business partners and suppliers.