MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Epo Tek OE132-43

Single Component

*HMIS: HEALTH-3 FIRE-1 REACTIVITY-0 Carcinogen: NTP (No) IARC (No) OSHA (No)

EPOXY TECHNOLOGY 14 FORTUNE DRIVE BILLERICA, MA 01821

EMERGENCY PHONE: US/CANADA: 800-255-3924 INT'L COLLECT: + 813-248-0585

DATE ISSUED: 7/24/13

REV:

* HMIS ratings are estimated by Epoxy Technology.

I. IDENTIFICATION & PHYSICAL DATA

PERCENT VOLATILE: NA
BOILING POINT: NA
VAPOR DENSITY: >Air
APPEARANCE: Clear Liquid

ODOR: Mild

VAPOR PRESSURE: NA
SOLUBILITY IN WATER: Low
EVAPORATION RATE: >BUAC
SPECIFIC GRAVITY: NA

II. HAZARDOUS INGREDIENTS CAS# WT %

2-Pyrrolidinone,1-(2-hydroxyethyl)- 3445-11-2 <5

III. FIRE & EXPLOSION DATA

FLASH POINT: >200 °F

EXTINGUISHING MEDIA: Dry chemical, foam, carbon dioxide.

UNUSUAL FIRE & EXPLOSION HAZARDS: Avoid fumes liberated by heat.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self contained breathing apparatus and complete personal

protective equipment. Remove all ignition sources. Use a water spray to cool fire exposed containers.

IV. REACTIVITY DATA

STABILITY: Stable HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Excessive heat.

MATERIALS TO AVOID: Acids, bases, oxidizing and reducing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Fumes produced when heated to decomposition may include

carbon monoxide, carbon dioxide and oxides of nitrogen.

To the best of our knowledge, the information contained herein is accurate. Epoxy Technology Inc., however, assumes no liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

V. HEALTH HAZARD DATA Epo Tek OE132-43

EFFECTS OF OVEREXPOSURE

INGESTION: May cause gastrointestinal irritation.
INHALATION: May cause respiratory tract irritation.
SKIN CONTACT: Can cause irritation and dermatitis.
EYE CONTACT: Irritating to the eyes. Can cause injury.

CHRONIC EFFECTS OF OVEREXPOSURE: May cause dermatitis.

EMERGENCY & FIRST AID PROCEDURES

EYE CONTACT: In case of eye contact, flush well with water. Get medical attention immediately.

 $\ensuremath{\mathsf{SKIN}}$ $\ensuremath{\mathsf{CONTACT:}}$ In case of skin contact, clean with soap and water. Do not use

solvents. Remove contaminated clothing.

INGESTION: Get medical attention immediately. Do not induce vomiting. **INHALATION:** Remove employee to fresh air. If discomfort persists, get medical

attention.

VI. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED: Eliminate ignition sources. Use eye and skin protection. Place leaking containers in a well ventilated area. Absorb spillage with inert material and dispose.

WASTE DISPOSAL METHOD: Incinerate or use hazardous waste treatment procedures that are in accordance with federal, state and local regulations.

VII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Wear a NIOSH-approved respirator whenever high level exposure to vapors or mist is anticipated.

VENTILATION: Local exhaust recommended for exposure control.

PROTECTIVE GLOVES: Impervious gloves - neoprene or equivalent. A combination of barrier cream and gloves is recommended.

EYE PROTECTION: Chemical splash goggles recommended.

OTHER PROTECTIVE EQUIPMENT: For operations where contact can occur, use a face shield and impervious apron. A safety shower and eye wash facility should be available.

VIII. SPECIAL PRECAUTIONS: Avoid contact with skin and eyes. Avoid breathing vapors. Keep containers closed when not in use. Remove all contaminated clothing immediately and wash. Wash skin thoroughly with soap and water after handling. Solvents should not be used to clean skin because of increased penetration potential - protective skin oils can be dissolved by solvents.

REGULATORY INFORMATION

EPOXY TECHNOLOGY 14 FORTUNE DRIVE BILLERICA, MA 01821 TEL: (978) 667 – 3805

PRODUCT NAME: OE132-43 DATE ISSUED: 7/24/13

1. SARA TITLE III SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right To Know Act of 1986 (40 CFR 372): None

2. TSCA Inventory Status

All the components of this product are listed on the TSCA Inventory.

3. RCRA Status

This product contains the following chemicals listed on the 40 CFR Part 261.33: None

4. CERCLA Status

This product contains the following chemicals listed on the 40 CFR Part 302.4: None

5. Transportation

Proper shipping name: CORROSIVE LIQUID, N.O.S. contains (N-CYCLOHEXYL-2-PYRROLIDONE)
Hazard class: 8
ID number: UN 1760
Packing group: II

The information contained herein is given in good faith. However, no guarantee or warranty of any kind expressed or implied is made with respect to this information.