Suzanne Miller

BREWER SCIENCE INC. SAFETY DATA SHEET

This Material Safety Data Sheet has been prepared to comply with the EC Directive, Canadian WHMIS and the OSHA Hazard Communication Standard.

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product Name: EXP03036

Manufacturer: Brewer Science, Inc. 2401 Brewer Drive

Information Phone Number: (573) 364-0300 Emergency Phone Number: (800) 255-3924

Rolla, MO 65401

MSDS Date of Preparation: 06/06/03 Product Use: Protective Coating Fax: (573) 368-3318

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name CAS# / EINECS# EU Classification (67/548/EEC) 1-Methoxy-2-propanol 107-98-2 / 203-539-1 80-95 R10 (Propylene glycol monomethyl ether, PGME) Water 7732-18-5 / 231-791-2 5-15 Not Applicable Polymer 0.5-1.5 Xi R41, R38 Proprietary

See Section 16 for further information on EU Classification.

This product may contain substances that are not listed on the EPA Toxic Substances Control Act Inventory. Only R&D activities can be carried out with this material. See Section 15 for additional information.

SECTION 3: HAZARDS IDENTIFICATION

Liquid with a solvent odor.

EMERGENCY OVERVIEW: Flammable liquid and vapor. May cause eye, skin, and respiratory irritation. May cause headache, dizziness, nausea and other symptoms of central nervous system depression.

EU Preparation Classification (1999/45/EC): Flammable R10

SECTION 4: FIRST AID MEASURES

Eye: Rinse thoroughly with water for at least 15 minutes, holding the eye lids open to be sure the material is washed out. Get immediate medical attention.

Skin: Remove contaminated clothing, Wash contact area thoroughly with soap and water. Get medical attention if irritation or symptoms of exposure develop. Launder clothing before re-use.

Inhalation: Remove victim to fresh air. Give artificial respiration if needed. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Ingestion: Do not induce vomiting unless directed to do so by medical personnel, Keep the victim calm and warm. Get immediate medical attention.

BSI Document No. F.7.6.1764.A

Page 1 of 5

SECTION 5: FIRE FIGHTING MEASURES

Flash Point: 32°C (90°F)

Flammable Limits: LEL: 1.5 vol % UEL: 10.9 vol %

Extinguishing Media: Use water fog or spray, alcohol foam, carbon dioxide or dry chemical.

Special Fire Fighting Procedures: Wear NIOSH approved, positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

Unusual Fire Hazards: Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. Vapors may form explosive mixtures with air in confined areas.

Hazardous Decomposition Products: Oxides of carbon, organic acid vapors and unknown materials.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Spill: Remove all ignition sources such as open flames, spark producing equipment, pilot lights, etc. Wear appropriate protective clothing to prevent eye and skin contact including impervious gloves, safety goggles and respirator if needed. Ventilate area. Cover with and inert absorbent material and collect into an appropriate container for disposal. Report spills and releases as required to appropriate authorities.

SECTION 7: HANDLING AND STORAGE

Handling: Avoid breathing vapors, acrosols and mists. Use with adequate ventilation. Avoid contact with the eyes, skin and clothing. Always wear impervious gloves, chemical safety goggles and protective clothing when handling this material. Wash thoroughly after handling. Do not eat, drink or smoke in the work area. Keep product away from heat, sparks, flames and all other sources of ignition. No smoking in storage or use areas. Keep containers closed when not in use.

Storage: Store in a cool, dry, well-ventilated location away from incompatible materials. Keep containers closed when not in

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	Exposure Limits	
1-Methoxy-2-propanol	100 ppm TLV-TWA, 150 ppm TLV-STEL 100 ppm DFG MAK 100 ppm EU-TWA, 150 ppm EU-STEL skin	
Water	None Established (PEL/TLV)	
Polymer	None Established (PEL/TLV)	

Ventilation: Use with adequate general or local exhaust ventilation to maintain exposure levels below the occupational exposure limits. Use explosion proof electrical equipment and wiring where required.

Respiratory Protection: If needed, a NIOSH approved respirator with organic vapor cartridges may be used. For higher exposures (greater than 10 times the TLV), a supplied air respirator may be required. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

Skin Protection: Impervious gloves are recommended. Based on available test data, 4H or Silver Shield gloves are suggested.

Eye Protection: Chemical safety goggles recommended.

Other Protective Equipment: Impervious clothing is recommended to prevent skin contact and contamination of personal clothing. An eye wash facility and safety shower should be available in the work area.

BSI Document No. F.7.6.1764.A

Page 2 of 5

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: Liquid with a solvent odor.

pH: Not available

Boiling Point: 120 - 150°C

Vapor Pressure: 12.5 mmHg @ 25°C (1-Methoxy-2-propanol)

Vapor Density: 3.12 (1-Methoxy-2-propanol)

Specific Gravity: Not available Melting Point: Not Applicable Water Solubility: Partially Soluble Evaporation Rate: Not available

SECTION 10: STABILITY AND REACTIVITY

Stability:

Stable: X

Unstable:

Incompatibility/Conditions to Avoid: Strong oxidizing agents, acids, bases, amines, alcohols. Keep away from heat, sparks, flames and other sources of ignition.

Hazardous Decomposition Products: Oxides of carbon, organic acid vapors and unknown materials.

Hazardous Polymerization: May Occur: Will not occur: X

SECTION 11: TOXICOLOGICAL INFORMATION

Potential Health Effects:

Eye: May cause mild to moderate eye irritation. Corneal injury is unlikely.

Skin: May cause mild irritation. 1-Methoxy-2-propanol may be absorbed through the skin causing symptoms of headache, dizziness, nausea, and drowsiness.

Inhalation: Inhalation of vapors, mists, or aerosols may cause nose and throat irritation with the possibility of central nervous system depression. Symptoms of central nervous system depression include headache, dizziness, drowsiness, nausea and

Ingestion: Swallowing may cause gastrointestinal irritation and central nervous system depression with symptoms similar to those described under inhalation.

Chronic Hazards: Chronic exposure may cause nervous system, kidney or liver effects based on studies with laboratory animals.

Carcinogen Status: None of the components of this product are listed as carcinogens by OSHA, IARC or NTP.

Medical Conditions Aggravated by Exposure: Pre-existing skin diseases.

Acute Toxicity Values:

1-Methoxy-2-propanol: Oral rat LD50 - 5660 mg/kg

Inhalation rat LC50 - 10,000 ppm/5 hr

Skin rabbit LD50 - 13 gm/kg

Polymer: No data available

SECTION 12: ECOLOGICAL INFORMATION

1-Methoxy-2-propanol: LC50 for fathcad minnow is 20800 mg/L and for daphnia magna is 23300 mg/L.

BSI Document No. F.7.6.1764.A

Page 3 of 5

SECTION 13: DISPOSAL INFORMATION

Dispose in accordance with all local, state and federal regulations.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name; 1-Methoxy-2-propanol Solution

ERG #129

DOT Hazard Class: 3, PG III UN Number: UN3092

DOT Labels Required (49CFR172.101): Flammable Liquid

Hazardous Substance (49CFR172.101): None

Reportable Quantity: N/A

IATA Shipping Name: 1-Methoxy-2-propanol Solution

IATA Hazard Class: 3, PG III UN Number: UN3092

IATA Hazard Labels Required: Flammable Liquid

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA 103 Reportable Quantity: Not applicable

SARA TITLE III:

Hazard Category for Section 311/312: Acute Health, Fire Hazard

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: One or more components may not be listed on the TSCA inventory. Only R&D activities may be carried out with this product and such activities must be performed by or under the direction of a technically

STATE REGULATIONS:

California Proposition 65: This products contain the following substances known to the State of California to cause cancer

INTERNATIONAL REGULATIONS:

European Community Labeling:

R10 Flammable

S51 Use only in well ventilated areas.

SECTION 16: OTHER INFORMATION

HMIS Ratings: Health - 2

Flammability - 3

Reactivity - 0

NFPA Ratings: Health - 2

Flammability - 3

Reactivity - 0

BSI Document No. F.7.6.1764.A

Page 4 of 5

EU Classes and Risk Phrases for Reference (See Sections 2 and 3):

XI Irritant

R10 Flammable

R41 Risk of serious damage to eyes..

R38 Irritating to skin.

This above information is believed to be correct but does not propose to be all inclusive and shall be used only as a guide. Brewer Science shall not be held liable for any damage resulting from handling or from contact with the above product.

BSI Document No. F.7.6.1764.A

Page 5 of 5