

P120-01-020

Issue: C

Rev Date: 01-06-05

Page: 1 of 6

PRODUCT NAME: Mechanical Pump Oil - Krytox® 1506, 1514, 1525

1. Product and Company Identification

Product Name:

Krytox® mechanical pump oils Grades 1506/1514/1525

Synonyms:

None

Item Numbers:

Grade 1506: H113-07-017; H113-07-018; H113-07-019; H113-07-020; H113-07-024;

H113-07-027.

Grade 1514: H113-08-017; H113-08-018; H113-08-019; H113-08-020; H113-08-021;

H113-08-024; H113-08-027.

Grade 1525: H113-09-017; H113-09-018; H113-09-019; H113-09-020; H113-09-024;

H113-09-027.

European Contact Details

BOC Edwards, Manor Royal, Crawley,

West Sussex, RH10 2LW, England

General enquiries

UK:

+44 (0)1293 528844

France:

+(33) 1 47 98 24 01

Germany:

+(49) 89-991918-0

Italy:

+(39) 0248-4471

US Contact Details

BOC Edwards, 301 Ballardvale Street,

Wilmington, MA 01887

General enquiries

+(1) 978-658-5410

Toll Free: 1-800-848-9800

24 h Emergency telephone number:

Chemtrec: 1-800-424-9300

2. Composition/Information on Ingredients

Ingredient	% Weight	CAS No	Hazard class*	Risk phrase*
Perfluoroalkylether	100	60164-51-4	Not applicable	Not applicable

^{*}Hazard class & Risk phrase. These columns are only completed for ingredients which are classified as hazardous under EU Directive (67/548/EEC, as amended) and are present in sufficient concentration to make the overall substance hazardous. In all other situations, the column will be completed as "Not applicable".

3. Hazards Identification

EMERGENCY OVERVIEW

This material when properly handled according to good working and hygienic practices is not dangerous to human health and the environment. Vapours which may irritate the respiratory system may be released above 290°C/554°F.

For short and long term exposure effects see Section 11 Toxicological data

DCC1 No: 705

Ref 2D01-010 form issue 1.2

Rev Date: 01-06-05

Page: 2 of 6

PRODUCT NAME: Mechanical Pump Oil - Krytox® 1506, 1514, 1525

Eye Effects:

Excessive exposure may cause irritation, discomfort, excessive lacrimation and blurred

vision.

Skin Effects:

Excessive exposure may cause irritation, discomfort and rash.

Ingestion/ Oral

No information available.

Effects:

Inhalation Effects:

Low volatility makes inhalation an unlikely hazard in normal use. The thermal decomposition

vapours of fluorinated polymers may cause polymer fume fever with flu-like symptoms in

humans, especially when smoking contaminated tobacco.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None known.

NFPA Hazard codes		HMIS Hazard codes		Rating System	
Health	1	Health	1	0 = No Hazard	
Flammability	0	Flammability	0	1 = Slight hazard	
Instability 0		Reactivity 0		2 = Moderate Hazard	
6				3 = Serious Hazard	
				4 = Severe hazard	

4. First Aid Measures

Eves:

Rinse with plenty of water. If irritation persists, consult a specialist.

Skin:

Wash off with soap and water. If irritation persists, seek medical attention.

Ingestion/Oral:

Rinse mouth. Drink water as a precaution. Do not induce vomiting without medical advice.

Consult a physician after significant exposure.

Inhalation:

Move to fresh air in case of accidental inhalation of vapours of decomposition products. If

breathing problems occur, a qualified individual should administer oxygen or artificial

respiration as indicated. Seek immediate medical attention.

Other Information:

Never to give anything by mouth to an unconscious person.

5. Fire Fighting Measures

Extinguishing Media:

The product does not burn. Select extinguishing media to suit other material(s)

involved.

Fire and Explosion Hazard:

Vapours which may irritate the respiratory system may be released above

290°C/554°F.

Special Protective Equipment

for Fire Fighters:

Fire fighters should wear a self-contained breathing apparatus (SCBA) which

meets appropriate standards operated in positive pressure mode. Skin protection

should be worn to protect from thermal combustion products.

For Flammability Properties - see Section 9

DCC1 No: 705

Ref 2D01-010 form issue 1.2

Rev Date: 01-06-05

Page: 3 of 6

PRODUCT NAME: Mechanical Pump Oil - Krytox® 1506, 1514, 1525

6. Accidental Release Measures

In the event of spillage:

- Wear personal protective clothing (see Section 8 Exposure Controls and Personal Protection).
- Recover released product and collect in a suitable container for reuse or disposal. Wash area to prevent slip hazard.
- · Avoid discharge into sewage systems, surface or underground waters and the soil.

7. Handling and Storage

Handling: Avoid temperatures > 290°C/554°F without adequate ventilation. Wear protective clothing (see Section 8). Avoid contact with eyes. Do not breath vapours or spray mists.

Storage: Keep tightly closed in a dry, cool well ventilated place. No special restrictions on storage with other products. Store in glass or polyethylene containers.

8. Exposure Controls/Personal Protection

Exposure Limits

Ingredient	ACGIH - TLV -	OSHA - PEL	Occupational Exposure Limits EH40 (UK)
Perfluoroalkylether	Not Applicable	Not Applicable	Not Applicable

Personal Protection:

Engineering Measures:

No specific measures required under normal conditions.

Respiratory Protection:

No specific measures required under normal conditions.

Hand/Skin Protection:

Wear impervious PVC gloves.

Eye/Face Protection:

Wear safety glasses.

Hygiene Measures:

Avoid contact with skin. Do not eat or smoke whilst using the product. Wash

hands before eating or smoking. Keep product away from tobacco products.

Other/General Protection:

None.



Rev Date: 01-06-05

Page: 4 of 6

PRODUCT NAME: Mechanical Pump Oil - Krytox® 1506, 1514, 1525

9. Physical and Chemical Properties

Appearance and Odour	Colourless, odourless, viscous liquid	Boiling Point	No data available	°C/°F
pH (as supplied)	Neutral	Freezing Point	No data available	°C/°F
Solubility in Water	Negligible	Auto Ignition	Not applicable	°C/ °F
Volatile Content by Volume	No data available	Flash Point	Does not burn	°C/°F
Specific Gravity	1.86 - 1.91 @ 24°C/75° F			
Vapour Pressure (mbar)	Grade 1506: 5.2x10 ⁻⁷ @ 20°C Grade 1514: 2.6x10 ⁻⁷ @ 20°C Grade 1525: 1.3x10 ⁻⁷ @ 20°C	Vapour Pressure (Torr)	Grade 1506: 3.9x10 ⁻⁷ @ 68°F Grade 1514: 1.0x10 ⁻⁷ @ 68°F Grade 1525: 1.9x10 ⁻⁷ @ 68°F	

10. Stability and Reactivity

Stability:

Stable.

Material/Conditions to Avoid:

Avoid temperatures above 290°C/554°F. No materials to be specifically avoided.

Hazardous Decomposition:

Vapours which may irritate the respiratory system may be released above

290°C/554°F.

11. Toxicological Information

For a comprehensive description for the various toxicological (health) effects which may arise if the user comes into contact with the substance or preparation refer to Section 3 Hazards Identification.

Animal Data:

ALD value:

Dermal: >17000mg/kg (rat)

Oral: >25000mg/kg (rat)

ALC value:

Inhalation /4h : >19.54mg/l (rat)

The figures stated above are for perfluoroalkylether.

Note: ALD/ALC: Average lethal dose/ average lethal concentration.

Carcinogenicity:

No information available.

12. Ecological Information

No information available.

DCC1 No: 705

Ref 2D01-010 form issue 1.2

P120-01-020

Issue: C

Rev Date: 01-06-05

Page: 5 of 6

PRODUCT NAME: Mechanical Pump Oil - Krytox® 1506.

13. Disposal Considerations

Waste from residue/unused products: dispose of as special waste in compliance with the Control of Pollution (Special Waste) Regulations 1980 (UK), or other relevant national or international regulations.

Contaminated packaging: if recycling is not practicable, dispose of in compliance with the Environmental Protection (Duty of Care) Regulations 1991 (UK), or other relevant national or international regulations.

14. Transport Information

This product is not regulated as dangerous under transport regulations.

PARAMETER	EUROPEAN	CANADIAN TDG	UNITED STATES DOT
Proper Shipping Name	Not applicable	Not applicable	Not applicable
Hazard Class	Not applicable	Not applicable	Not applicable
Identification Number	Not applicable	Not applicable	Not applicable
Shipping Label	Not applicable	Not applicable	Not applicable

15. Regulatory Information

European Regulatory Information

This product has been classified in accordance with the Dangerous Substances Directive (67/548/EEC, as amended) and the Preparations Directive (88/379/EEC, as amended), implemented in the UK as the Chemical (Hazard Information and Packing) Regulations 1994 (CHIP, as amended).

Classified as dangerous to supply:

Risk Phrases:

Not applicable

Safety Phrases:

Not applicable

Symbols:

None

United States Regulatory Information

All ingredients contained in this product are included on the EPA TSCA Chemical Substance Inventory.

SARA TITLE III - SECTION 313 SUPPLIER NOTIFICATION:

This product does not contain toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and 40 CFR Part 372.

This product does not contain ingredients known to the state of California to cause cancer or reproductive toxicity.

Canadian Regulatory Information

All ingredients contained in this product are included on the Canadian DSL.

WHMIS Classification: D2B

DCC1 No: 705

Ref 2D01-010 form issue 1.2

Rev Date: 01-06-05

Page: 6 of 6

PRODUCT NAME: Mechanical Pump Oil - Krytox® 1506, 1514, 1525

16. Other Information

This MSDS is compiled in accordance with ANSI Z400.1 and the EU Safety Data Sheet Directive 91/155/EEC. Sources of information for this data sheet:

- DuPont Safety Data Sheet for Krytox® Series 1500, 1600,16000 and 16000N. Reference: 000001458/N/GB. Revision Date: 29 March, 1994.
- Edwards Publication 'Fluids and Sealants'. Publication number 09-H021-20-895.
- · National Library of Medicine (NLM) electronic databases (HSDB, RTECS, CHEMID, Toxline)

Glossary: CAS, Chemical Abstracts Service; NFPA, National Fire Protection Association; HMIS, Hazardous Material Information Service; LD, Lethal Dose; LC, Lethal Concentration; ACGIH, American Conference of Governmental Industrial Hygienists; TLV, threshold limit value; OSHA, Occupational Safety and Health Administration, US department of Labour; PEL, Permissible exposure limit; EH40 (UK), HSE Guidance Note EH40 Occupational exposure limits; PPM, parts per million; TWA, Time-Weighted Average; STEL, Short Term Exposure Limit; Canadian TDG, Canadian Transportation of Dangerous Goods; US DOT, US Department of Transportation.

HSDB, Hazardous Substances Data Bank; RTECS, Registry of Toxic Effects of Chemical Substances; CHEMID, Chemical Identification; DSL, Domestic Substances List; TSCA, Toxic Substances Control Act Public Law 94-469: CERCLA, Comprehensive Environmental Response, Compensation and Liability Act; EPCRA. Emergency Planning and Community Right-to-Know Act; CAA, Clean Air Act; US, SARA (Title III), Superfund Amendments and Reauthorization Act.; SARA 313, Superfund Amendments and Reauthorization Act, Section 313; EHS, Extremely Hazardous Substance; WHMIS, Workplace Hazardous Materials Information System.

Revisions

Although the information and recommendations in this data sheet are to the best of our knowledge correct, it is recommended that you make your own determination of the material's suitability for your purpose before you use it. The information contained in this data sheet has been reproduced from the manufacturers data, the accuracy of this information is the responsibility of the manufacturer. BOC Edwards accept no responsibility for damage of any nature resulting from the use of, or the reliance upon this data sheet.

Krytox® is a registered trademark of DuPont Dow Elastomers.

DCC1 No: 705

Ref 2D01-010 form issue 1.2