SIGMA-ALDRICH

sigma-aldrich.com

SAFETY DATA SHEET

Version 5.10 Revision Date 09/29/2015 Print Date 10/29/2015

1. PRODUCT AND COMPANY IDENTIFICATION

1.1	Product identifiers Product name	:	Methyl methacrylate
	Product Number Brand Index-No.	:	W400201 Aldrich 607-035-00-6
	CAS-No.	:	80-62-6
1.2	Relevant identified uses o	f th	e substance or mixture and uses advised against
	11 00 1		

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company	: Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone Fax	: +1 800-325-5832 : +1 800-325-5052

1.4 Emergency telephone number

Emergency Phone # : (314) 776-6555

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Skin irritation (Category 2), H315 Skin sensitisation (Category 1), H317 Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335 Acute aquatic toxicity (Category 3), H402

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word	Danger
Hazard statement(s) H225 H315 H317 H335 H402	Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. Harmful to aquatic life.
Precautionary statement(s) P210 P233	Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed.

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing.
	Rinse skin with water/shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for
	breathing. Call a POISON CENTER or doctor/ physician if you feel
	unwell.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to
	extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS Lachrymator.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Formula	:	C ₅ H ₈ O ₂
Molecular weight	:	100.12 g/mol
CAS-No.	:	80-62-6
EC-No.	:	201-297-1
Index-No.	:	607-035-00-6

Hazardous components

Classification	Concentration
Flam. Liq. 2; Skin Irrit. 2; Skin Sens. 1; STOT SE 3; Aquatic Acute 3; H225, H315, H317, H335, H402	<= 100 %
	Flam. Liq. 2; Skin Irrit. 2; Skin Sens. 1; STOT SE 3; Aquatic Acute 3; H225, H315, H317,

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed No data available

5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture Carbon oxides

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Flash back possible over considerable distance.Container explosion may occur under fire conditions.Use explosionproof equipment.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Storage class (TRGS 510): Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis				
Methyl methacrylate	80-62-6	TWA	50 ppm	USA. ACGIH Threshold Limit Values (TLV)				
	Remarks	Dermal Sens	Dermal Sensitization					
		Upper Respiratory Tract irritation						
		Eye irritation						
		Pulmonary e						
			body weight effects 2015 Adoption					
			ble as a human ca	rcipogen				
		TWA	50.000000 ppm	USA. ACGIH Threshold Limit Values				
		IVVA	50.00000 ppm	(TLV)				
	-	Upper Respi	ratory Tract irritati					
		Eye irritation						
		Pulmonary e						
		body weight						
				nclosed are those for which changes				
		are propose		noiseed are there for which changes				
			of Intended Chang	es (NIC)				
			ble as a human ca					
		Sensitizer		liciliogen				
		STEL	100.000000	USA. ACGIH Threshold Limit Values				
				(TLV)				
			ppm					
	-	Upper Resp	ratory Tract irritati	on				
		Eye irritation	Upper Respiratory Tract irritation					
		Pulmonary edema body weight effects Adopted values or notations enclosed are those for which chang are proposed in the NIC						
			es (NIC)					
			See Notice of Intended Changes (NIC) Not classifiable as a human carcinogen					
		Sensitizer	liciliogen					
		STEL	100 ppm	USA. ACGIH Threshold Limit Values				
		STEE		(TLV)				
		Dermal Sens	sitization					
			Jpper Respiratory Tract irritation					
		Eye irritation						
		Pulmonary edema						
		body weight effects						
			2015 Adoption					
			ble as a human ca	arcinogen				
	1	TWA	100.000000	USA. Occupational Exposure Limits				
				(OSHA) - Table Z-1 Limits for Air				
			ppm 410.000000	Contaminants				
	+	The volue in	mg/m3	l mata				
			mg/m3 is approxi	USA. NIOSH Recommended				
		TWA	100.000000					
			ppm	Exposure Limits				
			410.000000					
			mg/m3					
		TWA	100 ppm 410 mg/m3	USA. NIOSH Recommended Exposure Limits				
	+	TWA	100 ppm	USA. Occupational Exposure Limits				
		IVVA		(OSHA) - Table Z-1 Limits for Air				
			410 mg/m3	Contaminants				
	+	The value in mg/m3 is approximate.						
	+	TWA	100 ppm	USA. OSHA - TABLE Z-1 Limits for				
			410 mg/m3	Air Contaminants - 1910.1000				
	<u> </u>		1410 mg/ms					

8.2 Exposure controls

Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Splash contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 66 min Material tested:Butoject® (KCL 897 / Aldrich Z677647, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: liquid Colour: colourless
b)	Odour	pungent
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -48 °C (-54 °F)
f)	Initial boiling point and boiling range	100 °C (212 °F)
g)	Flash point	9 °C (48 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower	Upper explosion limit: 12.5 %(V)

	flammability or explosive limits	Lower explosion limit: 2.12 %(V)
k)	Vapour pressure	37 hPa (28 mmHg) at 20 °C (68 °F)
I)	Vapour density	3.46 - (Air = 1.0)
m)	Relative density	0.936 g/mL at 25 °C (77 °F)
n)	Water solubility	15.3 g/l at 20 °C (68 °F)
o)	Partition coefficient: n- octanol/water	log Pow: 1.38
p)	Auto-ignition temperature	400 °C (752 °F) at 1,013.25 hPa (760.00 mmHg)
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Oth	ner safety information	
	Surface tension	28 mN/m at 20 °C (68 °F)
	Relative vapour density	3.46 - (Air = 1.0)

10. STABILITY AND REACTIVITY

10.1 Reactivity

9.2

No data available

10.2 Chemical stability

Polymerizes with evolution of heat. Avoid contact with incompatible materials. Unless inhibited, product can polymerize, raising temperature and pressure, possibly rupturing container. Check inhibitor content often adding to bulk liquid if needed. Do not blanket or mix with oxygen-free gas as it renders inhibitor ineffective. Stable under recommended storage conditions. Contains the following stabiliser(s): Mequinol (<=30 ppm)

10.3 Possibility of hazardous reactions Polymerises readily unless inhibited.Vapours may form explosive mixture with air.

10.4 Conditions to avoid

May polymerize on exposure to light. Heat, flames and sparks.

- **10.5** Incompatible materials Oxidizing agents, Peroxides, Amines, Bases, acids, Reducing agents, Halogens
- **10.6 Hazardous decomposition products** Other decomposition products - No data available In the event of fire: see section 5

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 7,900 mg/kg

LC50 Inhalation - Rat - 4 h - 78,000 mg/m3

LD50 Dermal - Rabbit - male - > 5,000 mg/kg (OECD Test Guideline 402)

No data available

Skin corrosion/irritation

Skin - Rabbit Result: Irritating to skin. - 4 h

Serious eye damage/eye irritation

Eyes - Rabbit Result: No eye irritation

Respiratory or skin sensitisation

in vivo assay - Mouse May cause allergic skin reaction. (OECD Test Guideline 429)

Germ cell mutagenicity

No data available

Ames test S. typhimurium Result: negative

OECD Test Guideline 478 Mouse - male Result: negative

Carcinogenicity

Carcinogenicity - Rat - male and female - Inhalation No significant adverse effects were reported

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

- IARC: 3 Group 3: Not classifiable as to its carcinogenicity to humans (Methyl methacrylate)
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity

No data available

No data available

Developmental Toxicity - Rat - Inhalation No significant adverse effects were reported

Specific target organ toxicity - single exposure May cause respiratory irritation.

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available

Additional Information

Repeated dose Rat - male - Oral - NOAEL : >= 124.1 mg/kg toxicity RTECS: OZ5075000

Central nervous system depression, Drowsiness, Irritability, Dizziness, Ataxia., narcosis, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Liver - Irregularities - Based on Human Evidence Liver - Irregularities - Based on Human Evidence

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Toxicity to fish	static test LC50 - Lepomis macrochirus (Bluegill) - 283 mg/l - 96 h
Toxicity to daphnia and other aquatic invertebrates	flow-through test EC50 - Daphnia magna (Water flea) - 69 mg/l - 48 h
Toxicity to algae	static test EC50 - Pseudokirchneriella subcapitata - > 110 mg/l - 72 h (OECD Test Guideline 201)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 14 d Result: 94 % - Readily biodegradable (OECD Test Guideline 301C)

12.3 Bioaccumulative potential

12.4 Mobility in soil

12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging

Dispose of as unused product.

14. TRANSPORT INFORMATION

DOT (US)

UN number: 1247 Class: 3 Packing group: II Proper shipping name: Methyl methacrylate monomer, stabilized Reportable Quantity (RQ): 1000 lbs

Poison Inhalation Hazard: No

IMDG

UN number: 1247 Class: 3 Packing group: II EMS-No: F-E, S-D Proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED

ΙΑΤΑ

UN number: 1247 Class: 3 Packing group: II Proper shipping name: Methyl methacrylate monomer, stabilized

15. REGULATORY INFORMATION

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

CAS-No. Revision Date

Methyl methacrylate	80-62-6	2007-07-01
SARA 311/312 Hazards Fire Hazard, Acute Health Hazard, Chronic Health Hazard		
Massachusetts Right To Know Components		
	CAS-No.	Revision Date
Methyl methacrylate	80-62-6	2007-07-01
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Methyl methacrylate	80-62-6	2007-07-01
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Methyl methacrylate	80-62-6	2007-07-01
California Prop. 65 Components		

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute	Acute aquatic toxicity
Flam. Liq.	Flammable liquids
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H402	Harmful to aquatic life.
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT SE	Specific target organ toxicity - single exposure

HMIS Rating

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	3
Physical Hazard	0
NFPA Rating Health hazard: Fire Hazard:	2 3

	·
Reactivity Hazard: 0)

Further information

Copyright 2015 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Preparation Information

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.10

Revision Date: 09/29/2015

Print Date: 10/29/2015