

Material Safety Data Sheet

May be used comply with
OSHA's Hazard Communication Standard
29 CFR 1910.1200. Standard must be
consulted for specific requirements

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List)

NEGATIVE RESIST NR71-1500P

Note: Blank spaces are not permitted. If any item is not applicable, or no
Information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name Futurrex, Inc.	Emergency Telephone Number 1-800-535-5053 (U.S. and Canada)	International Emergency Phone Number +1-352-323-3500
Address (Number, Street, City, State and ZIP Code) 24 Munsonhurst Road	Telephone Number for Information 1-888-999-4188	Email: info@futurrex.com
Franklin , New Jersey 07416	Date Prepared 10/28/2011	
	Signature of Prepare (optional)	

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity: Common Name(s))	OSHA PEL	ACGIH TLV	CAS No.	Concentration (%)
Gamma-Butyrolactone	Not established		96-48-0	50-70
Resins	N.A.	N.A.	*	34-40
Sensitizers	N.A.	N.A.	*	<16

*All Components of the product are registered in the Chemical Substance Inventory according with the Toxic Substance Control Act.

Section III - Physical/Chemical Characteristics.

Boiling Point (°C)	204-206	Specific Gravity (H2O=1)	>1
Vapor Pressure (milibars) (20°C)	0.4	Melting Point (°C)	-43.5
Vapor Density (AIR-1)	>1	Evaporation Rate (Butyl Acetate=1)	<1

Solubility in Water

Negligible

Appearance and Odor

Yellow liquid. Characteristic odor.

Section IV- Fire and Explosion Hazard Data

Flash Point (Method Used) 100-101°C (DIN 51 758)	Flammable Limits. (% volume in air)	LEL 2.7	UEL 15.6
---	--	------------	-------------

Extinguishing Media

Carbon dioxide, dry chemical media, alcohol-type or all-purpose-type foam.

Special Fire Fighting Procedures.

Use water spray to cool fire-exposed containers and structures. Use self contained breathing apparatus and protective coating.

Unusual Fire and Explosion Hazard

Flammable vapors may be heavier than air and may travel long distance along the ground before igniting and may flash back to the vapor source.