Material Safety Data Sheet

May be used comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements

U.S.Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

IDENTITY (As Used on Label and List)		Note: Blank space	Note: Blank spaces are not permitted. If any item is not applicable, or no			
NEGATIVE RESIST NR9-1500PY		-	Information is available, the space must be marked to indicate that.			
Section I						
Manufacturer's Name		Emergency Telen	hone Numbe	≏r	International Emergency Phone Number	
Futurrex, Inc.			Emergency Telephone Number 1-800-535-5053 (U.S. and Canada)		+1-352-323-3500	
Address (Number, Street, City, State and Z	Telephone Number for Information			Email:		
24 Munsonhurst Road	1-888-999-4188			info@futurrex.com		
		Date Prepared				
Franklin , New Jersey 07416		10/28/2011				
		Signature of Prepare (<i>pptional</i>)				
		eignatare er rep)		
Section II - Hazardous Ingredients/Identi	v Information					
Hazardous Components (Specific Chemica	Identity: Common Name(s)) C	SHA PEL	ACGIH TLV	CAS Number % (optional)	
		3/) 0		//OOIITTEV		
Cyclohexanone		2	5 ppm	25ppm	108-94-1	
		L	o ppin	2000	100 04 1	
Resins		N	.A.	N.A.	*	
				н .л.		
Sensitizers		Ν	.A.	N.A.	*	
Sensilizers		IN	.A.	N.A.		
***		1	P 20 0	Ta is O have		
*All Components of the product are register		ince Inventory accord	ding with the	e Toxic Substa	nce Control Act.	
Section III - Physical/Chemical Characteristics.						
Boiling Point		Specific Gravity (H	120=1)			
(°C)	155				<1	
Vapor Pressure (mm Hg)		Melting Point				
(20°C)	2	(°C)			-47	
Vapor Density (AIR-1)		Evaporatiion Rate				
	3.4	(Butyl Acetate=1)			0.31	
Solubility in Water						
Negligible						
Appearance and Odor						
Yellow liquid. Characteristic odor.						
Section IV- Fire and Explosion Hazard Da	ata	-		-		
Flash Point (Method Used)		Flammable Limits		LEL	UEL	
44°C (TCC)		(% volume in air)		1.1	12.8	
Extinguishing Media						
Carbon dioxide, dry chemical media, alcohol-type or all-purpose-type foam.						
Special Fire Fighting Procedures.						
Use water spray to cool fire-exposed containers and structures. Use self contained breathing apparatus and protective coating.						
Unusual Fire and Explosion Hazard						
Flammable vapors may be heavier than air and may travel long distance along the ground before igniting and may flash back to the						
vapor source.						